

# Kramer VS-1616DN-EM 2x2 to 16x16 Modular 4K60 4x2x0 Multi-Format Managed Digital Matrix Switcher

## INPUTS

- 2 to 16 (in increments of 2) of various inputs
- See ACCESSORIES & RELATED PRODUCTS

## OUTPUTS

- 2 to 16 (in increments of 2) of various outputs
- See ACCESSORIES & RELATED PRODUCTS

## MAX. DATA RATE

- 10.2Gbps (3.4Gbps per graphic channel) depending on the cards used

## MAX RESOLUTION

- Up to 4K@60Hz (4:2:0)

## CONTROLS

- Front panel buttons, infrared remote control transmitter, RS-232, Ethernet, mini USB port, in/out audio testing jacks, and reset button (for future use)

## SWITCHING

- Confirm or At Once for immediate switching

## OPERATING TEMPERATURE

- 0° to +40°C (32° to 104°F)

## STORAGE TEMPERATURE

- -40° to +70°C (-40° to 158°F)

## HUMIDITY

- 10% to 90%, RHL non-condensing

## POWER CONSUMPTION

- 100-240V AC, 50/60Hz, 135VA

## INCLUDED ACCESSORIES

- Power cord, infrared remote control transmitter

## PRODUCT DIMENSION

- 19" x 14.17 x 4U (43.6cm x 36.00cm 17.70cm) W, D, H

## PRODUCT WEIGHT

- 6.7kg (14.8lbs) approx

## SHIPPING DIMENSION

- 57.00cm x 48.00cm x 28.00cm (22.44" x 18.90" x 11.02" ) W, D, H

## SHIPPING WEIGHT

- 8.0kg (17.7lbs) approx