



# KRAMER

## VS-21DT

2x1 4K60 4:2:0 HDCP 2.2 HDMI Auto  
Switcher over HDBaseT

| HDMI | HDCP Compliant | HDBaseT  
| 4K/60 UHD (4:2:0) | HDCP 2.2 Compatible



VS21DT is a highperformance automatic switcher for 4K, HDBaseT, HDMI 1.4, HDCP 2.2 video signals. Offering priority and lastconnected switching options, it automatically switches according to the selected switching scheme based on active video signal detection

## FEATURES

- Max. Data Rate - 8.91Gbps (2.97Gbps per data channel)
- Max. Resolution - 4K@60Hz (4:2:0)
- HDMI 1.4 & HDCP 2.2 Compliant
- Supports up to 40m reach at 4K@60Hz (4:2:0)
- Kramer Equalization and re-Klocking Technology
- HDTV Compatible
- 3D Pass-Though



# KRAMER

## TECHNICAL SPECIFICATIONS

2 HDMI	On female HDMI connectors
1 HDBT	On an RJ45 connector
Max. Data Rate	8.91Gbps (2.97Gbps per graphic channel)
Max. Resolution	4K@60Hz (4:2:0)
Standards Compliance	HDCP 2.2 (does not support conversion to HDCP 1.4), HDMI 1.4
Controls	DIPswitches for selecting switching mode (Priority/Last Connected), contact closure connectors for remote control switches
Indicators	Active input, switching mode (Priority/Last Connected) and ON
Source	5V DC
Consumption	1A
REGULATORY CERTIFICATION:	EMC EN 55032;IEC 609501(ed.2);IEC 609501(ed.2)am1;IEC 609501(ed.2)am2
Operating Temperature	0° to +40°C (32° to 104°F)
Storage Temperature	40° to +70°C (40° to 158°F)
PRODUCT DIMENSION:	12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96" ) W, D, H
PRODUCT WEIGHT:	0.2kg (0.4lbs) approx
SHIPPING DIMENSION:	15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43" ) W, D, H
SHIPPING WEIGHT:	0.5kg (1.1lbs) approx
Humidity	10% to 90%, RHL noncondensing
Included	5V DC power adapter
Optional	RK3T 19" rack adapter

