

Kramer VS-21DT 2x1 4K60 4x2x0 HDCP 2.2 HDMI Auto Switcher over HDBaseT

Inputs	2 HDMI: On female HD MI connectors
Outputs	1 HDBT: On an RJ-45 connector
Video	Max. Data Rate: 8.91 Gbps (2.97Gbps per graphic channel) Max. Resolution: 4K@60Hz (4:2:0) Standards Compliance: HDCP 2.2 (does not support conversion to HDCP 1.4), HDM11.4
UserInterface	Controls: DIP-switches for selecting switching mode (Priority/Last Connected), contact closure connectors for remote control switches Indicators: Active input, switching mode (Priority/Last Connected) and ON
Power	Source: 5V DC Consumption: 1A
REGULATORYCERTIFI	EMC EN 55032 EC 60950-1 (ed.2) EC 60950-1 (ed.2)am1 EC 60950-1 (ed.2)am2
EnvironmentalConc	Operating Temperature: 0° to -40eC (32e to 104aF) Storage Temperature: -40° to -70aC (-40a to 158aF) Humidity: 10% to 90%, RHL non-condensing
Accessories	Included: 5V DC power adapter Optional: RK-3T 19" rack adapter
PRODUCT DIMENSIONS	12.00cm x 7.15cm x 2.44cm (4.72" x 2.81 " x 0.96") W, D, H
PRODUCT WEIGHT	0.2kg (0.4lbs) approx
SHIPPING DIMENSIONS	15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H
SHIPPING WEIGHT	0.5kg (1.1 lbs) approx