

Kramer VS-3232DN-EM 4x4 to 32x32 Modular 4K60 4x2x0 Multi Format Managed Digital Matrix Switcher

| | |
|--------------------|--|
| Inputs | 4 to 32 (in increments of 4) of various inputs See ACCESSORIES & RELATED PRODUCTS |
| Outputs | 4 to 32 (in increments of 4) of various outputs See ACCESSORIES & RELATED PRODUCTS |
| %strMAXRESOLUTION | Up to UXGA 1080p, 1920x1200 |
| %strCONTROLS% | Front panel buttons, infrared remote control transmitter, RS-232, Ethernet, mini USB port, in/out audio testing jacks, and reset button (for future use) |
| %strSWITCHING% | Confirm or At Once for immediate switching |
| %strPOWERCONSUMF | 100-240V AC, 50/60Hz, 320VAwith optional Hot-Swappable redundant power supply |
| %strMAX.NOISE% | 42dB |
| %StrSTANDARDSCOM | UL 60950, IEC 60950, EN 55022, EN 55024, EN 55032, IEC 61000, CFR 47 FCC part 15, V-3/2015.4 (VCCI), IEC 60601-1 (medical) |
| %StrINCLUDEDACCESJ | Power cord, null-modem adapter, infrared remote control transmitter |
| %strOPTIONS% | PS-1 DN redundant power supply |
| %strPRODUCTDIMENf | 19" x 14.17 x 6U (43.6cm x 36.00cm 26.60cm) W, D, H |
| %strPRODUCTWEIGH1 | 14.2kg (31.4lbs) approx |
| %strSHIPPINGDIMENS | 60.00cm x 49.30cm x 39.00cm (23.62" x 19.41" x 15.35") W, D, H |
| %strSHIPPINGWEIGHI | 15.7kg (34.6lbs) approx |