

Kramer VS-8UFX 8-Port 12G SDI Matrix Switcher with Interchangeable Inputs and Outputs

%strPorts%	8 12G HD-SDI/HD-SDI/SDI video: On BNC connectors (by default, 1 to 4 are set as inputs and 5 to 8 are set as outputs) 1 Genlock: 75CI on a BNC connector
%strSTANDARDSCOMPLIAN	12G-SDI: SMPTE ST-2082-1 3G HD-SDI: SMPTE 424M HD-SDI: SMPTE 292M SDI: SMPTE 259M/344M
%strVideo%	Max. Resolution: 4K@60Hz (4:2:2) Max. Data Rate: 12Gbps
%strUserInterface%	Controls: Front Panel Buttons, R5-232. Ethernet, Web pages Indicators: LCD display. Power LED
%strExtensionLine%	SD: Up to 300m 1.5GHz HD: Up to 200m 3GHz HD: Up to 100m 6GHz HD: Up to 100m 12GHz UHD: Up to 80m
%strCOUPLING%	AC
%strPower%	Source: 100-240VAC Consumption : 33VA max
%strEnclosure%	Size: 19", 1U Type: Aluminum Cooling: Fan ventilation
%strEnvironmentalConditio	Operating Temperature: 0C to +405C (32c to 104CF) Storage Temperature: -405 to +705C {-40c to 1585F) Humidity: 10% to 90%. RHL non-condensing
%strRegulatoryCompliance(Safety: CE Environmental: RoHs, WEEE
Accessories	Included: Power cord, rack ears
%strPRODUCTDIMENSION<K	43.64cm x 18.30cm x 4.36cm (17.18' x 7.20" x 1.72") W. D. H
%strPRODUCTWEIGHT%	1.7kg (3.7lbs) approx
%strSHIPPINGDIMENSION%	55.00cm x 27.60cm x 10.70cm (21.65* x 10.87" x 4.21*) W. D. H
%strSHIPPINGWEIGHT%	2.7kg (6.0lbs) approx
%strExtendedUSB%	Host Compliance: 1.1 and 2.0 Max Extended Line Rate Bandwidth: 127Mbps {out of max 480 USB) Max Devices: 7 Max Hubs: 2 Max Ports per Hub: 5
%strExtendedEthernet%	Max Transmission Bandwidth: 100Mbps
%strExtendedRS-232%	Baud Rate: 300 to 57600
%strControlRS-232%	Baud Rate: 115200
%strSupportedPCWebBrow;	Windows 7 and Higher: Internet Explorer (32/64 bit) version 10. Firefox version 30. Chrome version 35 MAC: Chrome version 35, Firefox version 30, Safari version 7 Optimal Resolution: 1920x1080 Minimal Resolution: 1024 x 768
%strPower%	Source: 100-240V AC, 50/60HZ Consumption: 250VA
%strEnclosure%	Size: 19" (W). 9.3" (H). 2U. rack mountable Type: Aluminum Cooling: Fan ventilation
%strEnvironmentalConditio	Operating Temperature: 0C to +405C {32c to 104CF) Storage Temperature: -405 to +705C {-40c to 1585F) Humidity: 10% to 90%. RHL non-condensing
%strRegulatoryCompliance(Safety: CE. UL Environmental: RoHs, WEEE
Accessories	Included: Power cord Optional: Recommended Kramer cables, see the CABLES tab
%strPRODUCTDIMENSION<K	19" x 12.05 x 2U (43.6cm x 30.60cm 8.80cm) W. D. H
%strPRODUCTWEIGHT%	3.9kg (8.6lbs) approx
%strSHIPPINGDIMENSION%	52.60cm x 47.50cm x 18.40cm (20.71' x 18.70" x 7.24") W. D. H
%strSHIPPINGWEIGHT%	5.4kg (11.8lbs) approx