

## Kramer VM-214DT 2x1x4 4K UHD HDMI and HDBaseT Distribution Amplifier

INPUTS:	1 HDMI connector, 1 HDBT twisted pair on an RJ-45 connector.
OUTPUTS:	1 HDMI connector, 4 HDBT twisted pair on RJ-45 connectors.
MAX.DATA RATE:	10.2Gbps (3.4Gbps per graphic channel, HDMI).
COMPLIANCE WITH HDMI STANDARDS:	Supports HDMI and HDCP.
CONTROLS:	Input select button, EDID select button, panel lock button, RS-232, local and remote IR controls.
INDICATOR LEDS:	IR communication, Power, IN 1 HDMI, IN 2 HDBT, OUTPUT 1,2,3,4 and 5, EDID TYPE Default, External, Output.
POWER CONSUMPTION:	100-240V AC 50/60Hz 16VA.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
COOLING:	Forced air, fan.
ENCLOSURE TYPE:	Aluminum.
RACK MOUNT:	With included rack "ears".
DIMENSIONS:	43.64cm x 18.3cm x 4.36cm, W, D, H (19" x 1U).
PRODUCT WEIGHT:	1.56kg (3.44lbs) approx.
SHIPPING WEIGHT:	2.7kg (5.95lbs) approx.
VIBRATION:	ISTA 1A in carton (International Safe Transit Association).
SAFETY REGULATORY COMPLIANCE:	CE.
ENVIRONMENTAL REGULATORY COMPLIANCE:	Complies with appropriate requirements of RoHs and WEEE.
INCLUDED ACCESSORIES:	Power cord, rack "ears".