

AJA FiDO-TR-12G 1-Channel 12G-SDI/LC Single-Mode LC Fiber Transceiver

Video Formats

- 270 Mbps - 12 Gbps, format agnostic

Video Input Digital

- 1-Channel Independent 12G-SDI BNC connector, SMPTE 259/292/424/2081/2082
- 1-Channel Independent Single Mode LC Fiber connector, SMPTE 297/259/292/424/2081/2082
- Nominal Wavelength:Tx 1260 nm (min), 1310 nm (typ), 1360 nm (max)
- Rx 1260 nm (min), 1620 nm (max)
- Optical Sensitivity: -10 dBm (min @12 Gbps), -14 dBm (min @ 3 Gbps)
- Optical Power: -5 dBm (min), 0.5 dBm (max)
- Overload Power: -2 dBm (min)
- Extinction Ratio: 5.4 dB (min)

Video Output Digital

- 1-Channel Independent 12G-SDI BNC connector, SMPTE-259/292/424/2081/2082
- 1-Channel Independent Single Mode LC Fiber connector, SMPTE-297/259/292/424/2081/2082
- Nominal Wavelength:Tx 1260 nm (min), 1310 nm (typ), 1360 nm (max)
- Rx 1260 nm (min), 1620 nm (max)
- Optical Sensitivity: -10 dBm (min @12 Gbps), -14 dBm (min @ 3 Gbps)
- Optical Power: -5 dBm (min), 0.5 dBm (max)
- Extinction Ratio: 5.4 dB (min)

Reclocking

- 270 Mbps, 1.483 Gbps, 1.485 Gbps, 2.967 Gbps, 2.970 Gbps, 5.934 Gbps, 5.940 Gbps, 11.868 Gbps, 11.880 Gbps - Auto Select
- All other rates are passed through and not reclocked

Size (w x d x h)

- 4.6" x 1.71" x .85" (117 x 43.5 x 21.6mm)

Power

- 4 watts max
- Uses 5-20VDC power (AJA power supply model DWP-U-R1 included)

Environment

- Safe Operating Temperature: 0 to 40 degrees C (32 to 104 degrees F)
- Safe Storage Temperature (Power OFF): -40 to 60 degrees C (-40 to 140 degrees F)
- Operating Relative Humidity: 10-90% noncondensing
- Operating Altitude: <3,000 meters (<10,000 feet)