

Kramer VM-2DT 1x2 4K60 4x2x0 Long-Reach HDBaseT DA

INPUT

- 1 HDBT connector

OUTPUTS

- 2 HDBT connectors

MAX. DATA RATE

- 10.2Gbps (3.4Gbps per graphic channel)

RANGE EXTENSION (INPUT OR OUTPUT EACH SIDE)

- Up to 40m (130ft) at 4K@60Hz (4:2:0),
- Up to 70m (230ft) at full HD (1080p @60Hz 36bpp),
- Note: When using Kramer HDBaseT cables

MAX. VIDEO RESOLUTION

- 4K@60Hz (4:2:0) 24bpp

COMPLIANCE

- Supports HDMI 2.0, HDCP 1.4 and HDBaseT 1.0

CONTROLS

- EDID setup button, indicator LEDs: OUTPUTS 1 and 2, LINK 1 and 2, active input, power on

OPERATING TEMPERATURE

- 0° to +40°C (32° to 104°F)

STORAGE TEMPERATURE

- -40° to +70°C (-40° to 158°F)

HUMIDITY

- 10% to 90%, RHL non-condensing

POWER

- Power source: 5.2V DC, 4A
- power consumption: 5V DC, 2.5A

INCLUDED ACCESSORIES

- Power supply

OPTIONS

- RK-T2B 19" rack adapter, Kramer HDBT cables

PRODUCT DIMENSION

- 18.75cm x 11.50cm x 2.54cm (7.38" x 4.53" x 1.00") W, D, H

PRODUCT WEIGHT

- 0.5kg (1.2lbs) approx

SHIPPING DIMENSION

- 34.50cm x 16.50cm x 5.20cm (13.58" x 6.50" x 2.05") W, D, H

SHIPPING WEIGHT

- 1.3kg (2.8lbs) approx