

TVlogic LVM-075A 7 inch Lightweight FHD 1920x1080 3G-SDI/HDMI LCD Monitor

LCD	Size	7"
	Resolution	1920 X 1080(16:9)
	Pixel Pitch	0.018(H) X0.018(W) mm
	Color Depth	16.7M (True 8bit)
	Viewing Angle	H : 170 degrees/V: 170degrees
	Luminance of white	600cd/m ² (Center)
	Contrast Ratio	800:1
	Display Area	155.52(H) X87.48(V) mm
Input Connector	3 X RCA	Analog Video Input
	2XBNC	SDI2 Channel Input
	1 XHDMI	HDMI Input
Output	1 XBNC	SDI Channel (Active Loop Through), HDMI-SDI (Conversion)
	1 XHDMI	HDMI-HDMI
Input Signal	Analog	CVBS/ S-Video / Component Video / RGB
	3G-SDI	2.970Gbps
	HD-SDI	1.485Gbps
	SD-SDI	270 Mbps
	HDMI	480i / 480p / 576i / 576p / 720p / 1080i / 1080p
Analog Input Spec	CVBS	1.0Vpp (with Sync)
	S-Video	1.0Vpp (Y with Sync), 0.286Vpp(C)
	Component	1.0Vpp (Y with Sync), 0.7Vpp (Pb.Pr)
SDI Input Signal Formats	SMPTE-425M-A/B	1080p(60/59.94/50/30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF) 1080i(60/59.94/50)
	SMPTE-274M	1080i (60/59.94/50)
		1080p (30/29.97/25/24/24sF/23.98/23.98sF)
	SMPTE-296M	720p (60/59.94/50)
	SMPTE-260M	1035i (60/59.94)
	SMPTE-125M	480i (59.94)
ITU-R BT.656	576i (50)	
Audio In	Embedded Audio / Analog Stereo (Phone Jack)	
Audio Out	Analog Stereo (Phone Jack), Internal speaker (Mixed Mono)	
Power	DC 12V	
Power Consumption (Approx.)	10 Watts(Typ.)	
Operating Temperature	0°C to 35°C (32°F to 95°F)	
Storage Temperature	-20°C to 60°C (-4°F to 140°F)	
Main Body Dimensions (mm/inch)	203 X 131 X 34.6 (7.99 X 5.16 X 1.36)	
Main Body Dimensions with stand (mm/inch)	240 X 145.8 X 69 (9.45 X 5.74 X 2.72)	
Box Dimensions (mm/inch)	330 X 250 X 180 (12.99 X 13.78 X 7.09)	
Weight	660g / 1.46 lbs / 940g / 2.07 lbs (with stand)	
Basic Accessories	DC Power adapter, AC Power Cord, Camera Mount Support	
Optional Accessories	Carrying Case, Rack Mountable Kit, Sun-Hood, External Acylic Protector, Tripod Ball Head, V-Mount, Gold Mount, External Tally	