

# Kramer VM-3DT 1x3 4K60 4x2x0 Long-Reach HDBaseT DA

## INPUT

- 1 HDBT on an RJ-45 female connector

## OUTPUTS

- 3 HDBT on RJ-45 female connectors

## MAX. DATA RATE

- 10.2Gbps (3.4Gbps per graphic channel)

## RANGE EXTENSION (INPUT OR OUTPUT EACH SIDE)

- Up to 40m (130ft) at 4K@60Hz (4:2:0),
- Up to 70m (230ft) at full HD (1080p @60Hz 36bpp),
- Note: When using Kramer HDBaseT cables

## MAX. VIDEO RESOLUTION

- 4K@60Hz (4:2:0) 24bpp

## COMPLIANCE

- Supports HDMI 2.0, HDCP 1.4 and HDBaseT 1.0

## CONTROLS

- EDID setup button, indicator LEDs: OUTPUTS 1-3
- LINK 1-3
- active input, power on

## OPERATING TEMPERATURE

- 0° to +40°C (32° to 104°F)

## STORAGE TEMPERATURE

- -40° to +70°C (-40° to 158°F)

## HUMIDITY

- 10% to 90%, RHL non-condensing

## POWER

- Power source: 5.2V DC, 4A
- power consumption: 5V DC, 3.2A

## ENCLOSURE

- Desktop size, Aluminum type

## COOLING

- Fan ventilation

## INCLUDED ACCESSORIES

- Power supply

## OPTIONS

- RK-1 19" rack adapter

## PRODUCT DIMENSION

- 18.75cm x 11.50cm x 2.54cm (7.38" x 4.53" x 1.00" ) W, D, H

## PRODUCT WEIGHT

- 1.0kg (2.1lbs) approx

## SHIPPING DIMENSION

- 34.50cm x 16.50cm x 5.20cm (13.58" x 6.50" x 2.05" ) W, D, H

**SHIPPING WEIGHT**

- 1.5kg (3.3lbs) approx