

# Kramer VM-3H2 4K HDMI 2.0 1x3 Distribution Amplifier

## INPUT

- 1 HDMI connector

## OUTPUTS

- 3 HDMI connectors

## PORT

- 1 RS-232 for firmware upgrade

## MAX. DATA RATE

- 17.82Gbps (5.94Gbps per graphic channel) supporting resolutions up to 4K @60Hz (4.4.4)

## COMPLIANCE WITH HDMI STANDARD

- Supports HDMI 2.0 and HDCP 2.2

## INDICATOR LEDS

- ON, IN, OUT 1 to 3

## OPERATING TEMPERATURE

- 0° to +40°C (32° to 104°F)

## STORAGE TEMPERATURE

- -40° to +70°C (-40° to 158°F)

## HUMIDITY

- 10% to 90%, RHL non-condensing

## POWER CONSUMPTION

- 5V DC, 730mA

## INCLUDED ACCESSORIES

- Power supply

## OPTIONS

- RK-T2B 19" rack adapter

## PRODUCT DIMENSION

- 18.75cm x 11.50cm x 2.54cm (7.38" x 4.53" x 1.00" ) W, D, H

## PRODUCT WEIGHT

- 0.4kg (0.9lbs) approx

## SHIPPING DIMENSION

- 35.10cm x 21.20cm x 7.20cm (13.82" x 8.35" x 2.83" ) W, D, H

## SHIPPING WEIGHT

- 1.0kg (2.1lbs) approx