

VM-400HDCPxI

1:4 DVI Distribution Amplifier

| DVI | HDCP Compliant | 4K/60 UHD (4:2:0)



The VM400HDCPxI is a 1:4 distributor for HDMI signals via single-link DVI. It takes one DVI input, equalizes and reclocks the signal and distributes it to four identical outputs. With the appropriate adapter, it distributes signals having resolutions up to 4K@60 UHD (4:2:0), WUXGA and 1080p

FEATURES

Max. Data Rate - 10.2Gbps (3.4Gbps per graphic channel) Resolution Support - Up to 4K@60 UHD (4:2:0), WUXGA and 1080p HDCP Compliance Kramer Equalization & re-Klocking[™] Technology - Rebuilds the digital signal integrity to travel longer distances I-EDIDPro[™] Kramer Intelligent EDID Processing[™] - An intelligent EDID handling and processing algorithm that ensures Plug and Play operation for HDMI systems Default EDID - For fast and efficient connection of the unit 3D Pass-Through USB Port - For firmware upgrading



TECHNICAL SPECIFICATIONS

INPUT:	1 DVII connector
OUTPUTS:	4 DVII connectors
PORT:	1 USB for firmware upgrade
MAX. DATA RATE:	10.2Gbps (3.4Gbps per graphic channel)
STANDARDS COMPLIANCE:	Supports HDMI and HDCP
CONTROLS:	EDID Setup button
INDICATOR LEDs:	IN, OUT 1 to 4 LEDs
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	40° to +70°C (40° to 158°F)
HUMIDITY:	10% to 90%, RHL noncondensing
PRODUCT DIMENSION:	18.75cm x 11.50cm x 2.54cm (7.38" x 4.53" x 1.00") W, D, H
PRODUCT WEIGHT:	0.5kg (1.0lbs) approx
SHIPPING DIMENSION:	34.50cm x 16.50cm x 5.20cm (13.58" x 6.50" x 2.05") W, D, H
SHIPPING WEIGHT:	1.0kg (2.2lbs) approx
POWER CONSUMPTION:	5V DC, 1.1A
INCLUDED ACCESSORIES:	Power supply