Kramer VM-400HDCPxI 1x4 DVI Distribution Amplifier

INPUT

• 1 DVI-I connector

OUTPUTS

• 4 DVI-I connectors

PORT

• 1 USB for firmware upgrade

MAX. DATA RATE

• 10.2Gbps (3.4Gbps per graphic channel)

STANDARDS COMPLIANCE

• Supports HDMI and HDCP

CONTROLS

• EDID Setup button

INDICATOR LEDS

• IN, OUT 1 to 4 LEDs

OPERATING TEMPERATURE

• 0° to +40°C (32° to 104°F)

STORAGE TEMPERATURE

• -40° to +70°C (-40° to 158°F)

HUMIDITY

• 10% to 90%, RHL non-condensing

POWER CONSUMPTION

• 5V DC, 1.1A

INCLUDED ACCESSORIES

• Power supply

PRODUCT DIMENSION

• 18.75cm x 11.50cm x 2.54cm (7.38" x 4.53" x 1.00") W, D, H

PRODUCT WEIGHT

• 0.5kg (1.0lbs) approx

SHIPPING DIMENSION

 $\bullet~$ 34.50cm x 16.50cm x 5.20cm (13.58" x 6.50" x 2.05") W, D, H

SHIPPING WEIGHT

• 1.0kg (2.2lbs) approx