

Kramer VM-4H2 4K HDMI 2.0 1x4 Distribution Amplifier

INPUT

- 1 HDMI connector

OUTPUTS

- 4 HDMI connectors
- PORT:1 RS-232 for firmware upgrade

MAX. DATA RATE

- 17.82Gbps (5.94Gbps per graphic channel) supporting resolutions up to 4K @60Hz (4.4.4)

COMPLIANCE WITH HDMI STANDARD

- Supports HDMI 2.0 and HDCP 2.2

INDICATOR LEDES

- ON, IN, OUT 1 to 4

OPERATING TEMPERATURE

- 0° to +40°C (32° to 104°F)

STORAGE TEMPERATURE

- -40° to +70°C (-40° to 158°F)

HUMIDITY

- 10% to 90%, RHL non-condensing

POWER CONSUMPTION

- 5V DC, 730mA

INCLUDED ACCESSORIES

- Power supply

OPTIONS

- RK-T2B 19" rack adapter

PRODUCT DIMENSION

- 18.75cm x 11.50cm x 2.54cm (7.38" x 4.53" x 1.00") W, D, H

PRODUCT WEIGHT

- 0.4kg (0.9lbs) approx

SHIPPING DIMENSION

- 34.50cm x 16.50cm x 5.20cm (13.58" x 6.50" x 2.05") W, D, H

SHIPPING WEIGHT

- 1.0kg (2.1lbs) approx