

# AVS-D2712SL

2 Megapixel Indoor/Outdoor, Full-Size Starlight Dome Camera



## FEATURES

- 1/2.8" 2.1Megapixel CMOS
- 2.7 ~ 12mm motorized lens, Auto Iris
- Max. IR LEDs length 150'/50m, Smart IR
- IP67, IK10, AC24V/DC12V

Revision: 1.0; Jun, 2016

### IC Realtime LLC

3050 N Andrews Avenue Extension  
 Pompano Beach, FL 33064  
 (866) 997-9009  
[www.icrealtime.com](http://www.icrealtime.com)



# SPECIFICATIONS

Camera	
Image Sensor	1/2.8" 2.1Megapixel CMOS
Effective Pixels	1945 (H)×1097 (V)
Electronic Shutter	1s~1/30,000s
Frame Rate	30/60fps@720P; 30fps@1080P
Synchronization	Internal
Min. Illumination	0.005Lux@F1.4; 0Lux IR LED's on
Video Output	1-channel BNC HDAVS high definition video output & CVBS standard definition video output

Camera Features	
Max IR LED Length	150/50m, Smart IR
Day/Night	Auto (ICR) / Color / B/W
Noise Reduction	2D/3D
OSD Menu	Support

Lens	
Focal Length	2.7mm ~ 12mm
<a href="#">Angle of View</a>	95° (W) ~ 36° (T)

Lens Type	Motorized / Auto-Iris (DC)
Mount Type	Φ14

Auxiliary Functions	
Alarm	1 channel in/out
Audio	1 channel in

General	
Power Supply	AC24V ±25% / DC12V ±25%
Power Consumption	Max 12.5W
Working Environment	-22°F ~ 140°F/-30°C ~ 60°C; < 95% RH (no condensation)
Transmission Distance	> 1500'/500m via 75-3 coaxial cable
Ingress Protection	IP67, IK10
Dimensions	Φ6.3"×4.6"/Φ159mm×117.9mm
Weight	1.98lbs/0.9kg
Material	Metal



Check Out Our Mobile App Lineup

## IC Realtime LLC

3050 N Andrews Avenue Extension  
Pompano Beach, FL 33064  
(866) 997-9009

[www.icrealtime.com](http://www.icrealtime.com)

