

Kramer VP-553XL Boardroom Presentation Switcher/Dual Scaler

INPUTS

- 3 HDMI connectors (HDMI, HDCP), 2 VGA on 15-pin HD connectors, 2 composite video on RCA connectors, 2 analog TP on RJ-45 connectors, 3 HDBT on RJ-45 connectors, 4 USB-B ports, 3 unbalanced analog audio on 3.5mm mini jacks for HDMI, 2 unbalanced analog audio on 3.5mm mini jacks for PC, 1 Aux in balanced stereo audio on 5-pin terminal block connectors, 2 balanced audio (L and R) RCA connectors for CV

OUTPUTS

- 1 HDBT on RJ-45 connector, 2 HDMI connectors (HDMI, HDCP), 1 USB port, 1 monitor out balanced stereo on a 5-pin terminal block connector, 1 line out balanced stereo on a 5-pin terminal block connector

OUTPUT RESOLUTIONS

- NATIVE, 640x480@60, 800x600@60, 1024x768@60, 1280x768@60, 1360x768@60, 1280x720@60, 1280x800@60, 1280x1024@60, 1440x900@60, 1400x1050@60, 1680x1050@60, 1600x1200@60, 1920x1080@60, 1920x1200@60, 720x480p@60, 1280x720p@60, 1920x1080i@60, 1920x1080p@60, 720x576p@60, 1280x720p@50, 1920x1080i@50, 1920x1080p@50

CONTROLS

- TP 1, TP 2, CV 1, CV 2, HDBT 1, HDBT 2, HDBT 3, PC 1, PC 2, HDMI 1, HDMI 2, HDMI 3, USB 1, USB 2, USB 3, USB 4 input selector buttons
- 2 blank, 2 mute, 2 freeze buttons
- menu, enter, menu arrows, reset to XGA/720p, OSD SELECT, 2 RS-232, IR, Ethernet, 2 level and EQ trimmers, line/mic selector switch, cond/dyn selector switch, mono/stereo selector switch, REM for muting audio

POWER CONSUMPTION

- 100-240V AC, 43VA max

OPERATING TEMPERATURE

- 0° to +40°C (32° to 104°F)

STORAGE TEMPERATURE

- -40° to +70°C (-40° to 158°F)

HUMIDITY

- 10% to 90%, RHL non-condensing

INCLUDED ACCESSORIES

- Power cord, rack "ears", IR remote control

OPTIONS

- Kramer BC-HDKat6a cable

PRODUCT DIMENSION

- 19" x 11.93 x 2U (43.6cm x 30.30cm 8.80cm) W, D, H

PRODUCT WEIGHT

- 3.7kg (8.0lbs) approx

SHIPPING DIMENSION

- 52.60cm x 47.50cm x 18.40cm (20.71" x 18.70" x 7.24") W, D, H

SHIPPING WEIGHT

- 5.1kg (11.2lbs) approx