

# Kramer VP-558 11x4 HDMI/HDBaseT Presentation Matrix Switcher/Scaler

- **INPUTS:**6 HDMI connectors, 1 VGA on a 15-pin HD connector, 4 HDBT on RJ-45 connectors, 4 USB ports, 6 unbalanced analog audio on 3.5mm mini jacks for HDMI, 1 unbalanced analog audio on a 3.5mm mini jack for PC, 1 aux in/mic balanced stereo audio on a 5-pin terminal block connector.
- **OUTPUTS:**4 HDBT on RJ-45 connectors, 4 HDMI connectors, 1 USB port, 4 audio out balanced stereo on 5-pin terminal block connectors, 4 audio out S/PDIF on RCA connectors, monitor out balanced stereo on a 5-pin terminal block connector, monitor out S/PDIF on an RCA connector, 1 stereo speaker output, 2x10W, on a 4-pin terminal block connector.
- **OUTPUT RESOLUTIONS:**NATIVE, 640x480@60, 800x600@60, 1024x768@60, 1280x768@60, 1360x768@60, 1280x720@60, 1280x800@60, 1280x1024@60, 1440x900@60, 1400x1050@60, 1680x1050@60, 1600x1200@60, 1920x1080@60, 1920x1200@60, 720x480p@60, 1280x720p@60, 1920x1080i@60, 1920x1080p@60, 720x576p@60, 1280x720p@50, 1920x1080i@50, 1920x1080p@50.
- **CONTROLS:**HDMI 1, HDMI 2, HDMI 3, HDMI 4, HDMI 5, HDMI 6, HDBT 1, HDBT 2, HDBT 3, HDBT 4, PC, USB 1, USB 2, USB 3, USB 4 input selector buttons; menu, enter, menu arrows, reset to XGA/720p, OSD SELECT, 2 RS-232, Ethernet, line/mic selector switch, cond/dyn (48V) selector switch, mono/stereo selector switch, REM for muting audio.
- **POWER CONSUMPTION:**100-240V AC, 70VA max.
- **OPERATING TEMPERATURE:**0° to +40°C (32° to 104°F).
- **STORAGE TEMPERATURE:**-40° to +70°C (-40° to 158°F).
- **HUMIDITY:**10% to 90%, RHL non-condensing.
- **DIMENSIONS:**19" x 14.4" x 2U (W, D, H) rack mountable.
- **WEIGHT:**5kg (11lbs) approx.
- **INCLUDED ACCESSORIES:**Power cord, rack "ears".
- **OPTIONS:**Kramer BC-HDKat6a cable.