

Kramer VP-771 9-Input ProScale Presentation Switcher/Scaler w Speaker Outputs

INPUTS:	2 HDMI (deep color) connectors, 2 VGA on 15-pin HD connectors, 1 component video on 3 RCA connectors, 2 composite video on RCA connectors, 1 DisplayPort connector, 1 SD/HD/3G HD-SDI plus loop a BNC connector, 2 HDMI, 2 VGA, 1 DP, 2 CV unbalanced stereo audio on 3.5mm mini jack connectors, 1 S/PDIF (for component video input) digital audio on an RCA connector, 1 mic on a 3.5mm mini jack connector.
OUTPUTS:	1 VGA on a 15-pin HD connector, 1 SD/HD/3G HD-SDI on a BNC connector, 1 HDMI (deep color) connector, 1 DGKat on an RJ-45 connector, 1 S/PDIF digital audio on an RCA connector, 1 unbalanced stereo audio on a 3-pin terminal block connector, 2x10W speaker amplifier balanced stereo audio on terminal block connectors.
COMPLIANCE WITH STANDARDS:	Supports HDMI (deep color) and HDCP; DisplayPort 1.1a.
OUTPUT RESOLUTIONS:	640x480@60, 640x480@75, 800x600@50, 800x600@60, 800x600@75, 1024x768@50, 1024x768@60, 1024x768@75, 1280x768@50, 1280x768@60, 1280x800@60, 1280x1024@50, 1280x1024@60, 1280x1024@75, 1360x768@60, 1366x768@50, 1366x768@60, 1400x1050@50, 1400x1050@60, 1600x900@60, 1600x1200@50, 1600x1200@60, 1680x1050@60, 1920x1200@60, 480i60, 480p60, 576i50, 576p50, 720p50, 720p59.94, 720p60, 1080p23.976, 1080p24, 1080p25, 1080p29.97, 1080p30, 1080p50, 1080p59.94, 1080p60, 2048x1080@60Hz, 2048x1080@50Hz
CONTROLS:	Front panel buttons, OSD, IR remote control, RS-232 on a 9-pin D-sub connector, Ethernet, contact closure.
POWER CONSUMPTION:	100-240V AC, 56VA max.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-49° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
DIMENSIONS:	19" x 9.3" x 1U (W, D, H) rack mountable.
WEIGHT:	2.5kg (5.5lbs) approx.
INCLUDED ACCESSORIES:	Power cord, rack “ears”, IR remote control.