

Kramer VS-211H2 2x1 Automatic 4K UHD HDMI Standby Switcher

INPUTS:	2 HDMI connectors.
OUTPUTS:	1 HDMI connector.
MAX. DATA RATE:	17.82GBPS (5.94Gbps per graphic channel).
MAX. RESOLUTION4K@60 UHD (4:	4:4).
COMPLIANCE WITH HDMI STANDARD:	HDCP and HDMI.
CONTROLS:	Status/priority DIP-switches, contact closure remote control.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
POWER CONSUMPTION:	5V DC, 400mA.
DIMENSIONS:	12cm x 7.15cm x 2.44cm (4.7" x 2.8" x 1.0") W, D, H.
WEIGHT:	0.156kg (0.34lbs) approx.
SHIPPING DIMENSIONS:	23.2cm x 12cm x 8.9cm (9.1" x 4.7" x 3.9") W, D, H.
SHIPPING WEIGHT:	0.625kg (1.38lbs) approx.
INCLUDED ACCESSORIES:	Power supply 5.2V DC/4A desktop.
OPTIONS:	RK-3T 19" rack adapter.