

Kramer VS-42UHD 4x2 4K UHD HDMI Matrix Switcher

INPUTS

- 4 HDMI connectors

OUTPUTS

- 2 HDMI connectors

PORTS

- 1 Ethernet on an RJ-45 connector
- 1 IR on a 3.5mm mini jack
- 12 remote selection contact-closure switches on 13 terminal block pins
- 1 serial port on a 3-pin terminal block
- 1 program port on a mini USB

BANDWIDTH

- Up to 8.91Gbps data rate (2.97Gbps per graphic channel)

COMPLIANCE WITH HDMI STANDARD

- HDMI and HDCP

RESOLUTION

- Up to UXGA
- 4K x 2K

SUPPORTED BAUD RATES

- 9600, 115200bps

SUPPORTED WEB BROWSERS

- The following operating systems and Web browsers are supported:
- Windows 7: Google Chrome v25, FireFox v15, Opera v12, Microsoft Internet Explorer v9
- Windows XP: Google Chrome v25, FireFox v15
- Apple Mac: Google Chrome v25, FireFox v20, Opera v12.14, Safari v6

POWER CONSUMPTION

- 5V DC, 880mA
- 100-240V AC, 65VA max

CONTROLS

- Front panel buttons, infrared remote control transmitter, RS-232, Ethernet, remote input selection switches

OPERATING TEMPERATURE

- 0° to +40°C (32° to 104°F)

STORAGE TEMPERATURE

- -40° to +70°C (-40° to 158°F)

HUMIDITY

- 10% to 90%, RHL non-condensing

INCLUDED ACCESSORIES

- Power supply, RC-IR3 remote control

OPTIONS

- External remote IR receiver cable, RK-1

PRODUCT DIMENSION

- 21.46cm x 16.30cm x 4.36cm (8.45" x 6.42" x 1.72") W, D, H

PRODUCT WEIGHT

- 0.9kg (2.1lbs) approx

SHIPPING DIMENSION

- 35.10cm x 21.20cm x 7.20cm (13.82" x 8.35" x 2.83") W, D, H

SHIPPING WEIGHT

- 1.8kg (3.9lbs) approx