

Barco R9023231 F32 SXGA 4200 lumens VizSim Bright Projector/No lens/Pearl White

Image Display	
Display System	1-Chip DLP
Native Resolution	1400 x 1050 (SXGA+)
Supported Resolutions	SXGA+
Max Brightness	4200 Lumens
Aspect Ratio	4:3
Contrast Ratio	7500:1
DLP Link 3D	Yes
Supported 3D Formats	Not Specified by Manufacturer
Color Depth	Not Specified by Manufacturer
Scan	Horizontal: 15 - 150 kHz Vertical: 48 - 190 Hz

Input/Output Connectors	
Inputs/Outputs	1 x DVI-D Video (Input) 1 x HDMI Video (Input) 1 x VGA (DE-15) Video (Input) 1 x 5BNC Video (Input) 1 x Component (3RCA) Video (Input) 1 x Composite (RCA) Video (Input) 1 x S-Video (4-Pin DIN) Video (Input) 1 x USB Control (Input) 1 x Ethernet (RJ45) Control (Input) 1 x RS-232C (Unspecified Connector) Control (Input) 1 x RS-232C (Unspecified Connector) Control (Output) 2 x 12 V Trigger Control (Input) 1 x 1/8" (3.5 mm) Mini Remote (Input)

General	
Light Source	Lamp (2 x UHP)
Lamp Power	300 W
Expected Lamp Life	Medium Brightness: 2000 Hours Low Brightness: 2500 Hours
AC Input Power	120 to 240 VAC, 50 / 60 Hz
Heat Dissipation	2900 BTU
Power Consumption	Not Specified by Manufacturer
Temperature	Operating 50 to 104°F (10 to 40°C) Humidity: 20 - 80% Storage -4 to 140°F (-20 to 60°C) Humidity: 10 - 90%
Dimensions (W x H x D)	20.1 x 9.2 x 14.8" / 510.0 x 233.0 x 376.0 mm
Weight	27.8 lb / 12.6 kg