



## VS-44DT

4x4 4K60 4:2:0 HDMI/HDBaseT  
ExtendedReach PoE Matrix Switcher

| HDMI | Ethernet - RJ-45 | HDBaseT



VS44DT is a 4x4 4K@60Hz (4:2:0) HDMI/HDBaseT matrix switcher that transmits video, audio, Ethernet, RS232 and IR signals over extended distances. The unit accepts up to four HDMI and four IR inputs as well as Ethernet and RS232 network and control. The inputs can be routed to any or all of the four HDBaseT outputs, the first two of which also have simultaneous HDMI outputs. VS44DT connects to compatible HDBaseT receivers such as, TP780RXR, TP580RXR and TP588D. It supports resolutions of up to 4K@60Hz (4:2:0) and WUXGA. The matrix is a PoE provider that provides power over Ethernet to compatible PoE receivers

### FEATURES

**Max. Data Rate** - 10.2Gbps (3.4Gbps per graphic channel)

**Max. Resolution** - 4K@60Hz (4:2:0) and WUXGA

**HDBaseT Range** - Up to 130m (430ft) at normal mode (2K), up to 100m at normal mode (4K); up to 180m (590ft) ultra mode (1080p @60Hz @24bpp) when using BCUNIKAT cables

**Cables** - For optimum range and performance, use the recommended Kramer cables available at [www.kramerav.com/product/VS44DT](http://www.kramerav.com/product/VS44DT)

**HDBaseT Extension** - Includes Video, Audio, Ethernet, RS232 and IR signals

**Outputs** - 4 HDBaseT with outputs 1 and 2 having simultaneous HDMI outputs

**PoE Support** - PoE provider to HDBaseT receivers such as the TP588D and TP780RXR

**HDTV Compatible**

**HDCP Compliant**

**EDID Capture** - Copies and stores the EDID from a display device

**HDMI Support** - 3D, Deep Color, x.v.Color™, Lip Sync, Dolby® TrueHD, Dolby Digital Plus, DTSHD® and 7.1 PCM

**Non-Volatile Memory** - Stores and recalls preset matrix configurations

**Automatic Output Shutdown** - If no input signal is detected after a configurable idle period

**Kramer Protocol 3000 Support**

**Lock Button** - Prevents unwanted tampering with the settings

**Flexible Control Options** - Embedded Web server, RS232, IR remote (included)

**Worldwide Power Supply** - 100240V AC



# KRAMER

## TECHNICAL SPECIFICATIONS

---

INPUTS:	4 HDMI on HDMI connectors, 5 IR on 3.5mm mini jack connectors
OUTPUTS:	2 HDMI connectors, 4 HDBaseT on RJ45 connectors, 5 IR on 3.5mm mini jack connectors, 1 unbalanced stereo audio on a 3.5mm mini jack connector
PORTS:	1 Ethernet on an RJ45 connector, 1 program on a USB connector, 1 RS232 control on a 3pin terminal block, 1 RS232 data on a 3pin terminal block
MAX. DATA RATE:	10.2Gbps (3.4Gbps per graphic channel)
SUPPORTED RESOLUTIONS:	VGA to WUXGA (reduced blanking), 4Kx2K @30Hz with Deep Color up to 36bpp
HDMI RANGE:	15m (49ft) @ 8bit resolution, 10m (33ft) @ 12 bit resolution
HDBaseT RANGE:	100m (328ft) 4K @30Hz 180m (590ft) 1080 @60Hz@24bpp
POWER CONSUMPTION:	100240V AC, 50/60Hz, 60VA
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F)
PRODUCT DIMENSION:	19" x 13.90 x 1U (43.6cm x 35.30cm 4.36cm) W, D, H
PRODUCT WEIGHT:	3.3kg (7.3lbs) approx
SHIPPING DIMENSION:	54.30cm x 44.20cm x 10.70cm (21.38" x 17.40" x 4.21" ) W, D, H
SHIPPING WEIGHT:	4.1kg (9.0lbs) approx
HUMIDITY:	10% to 90%, RHL noncondensing
COOLING:	Fan
ENCLOSURE TYPE:	Aluminum chassis
VIBRATION:	ISTA 1A in carton (International Safe Transit Association)
SAFETY REGULATORY COMPLIANCE:	CE
ENVIRONMENTAL REGULATORY COMPLIANCE:	Complies with appropriate requirements of RoHs and WEEE
INCLUDED ACCESSORIES:	Rack "ears", IR blaster, IR receiver RCIR3 remote control transmitter

