

Kramer VS-44UHDA 4x4 4K60 4x2x0 HDMI Matrix Switcher with Audio Embedding/De-Embedding

INPUTS

- 4 HDMI connectors, 4 unbalanced stereo audio on 3.5mm mini jacks

OUTPUTS

- 4 HDMI connectors, 4 balanced audio stereo output on a 5-pin terminal blocks (+4dBu nominal)

PORTS

- 1 USB, 1 RS-232, 1 Ethernet, 1 USB for powering an external device

COMPLIANCE WITH HDMI STANDARD

- Supports HDMI and HDCP

OUTPUT RESOLUTIONS

- Up to 4K@60Hz (4:2:0) and 4K@30Hz (4:4:4)

CONTROL

- Front panel buttons, 7-segment display, AFV and breakaway buttons (VIDEO, A-AUDIO and D-AUDIO), STO-RCL, LOCK, PATTERN-MUTE buttons, RS-232, Ethernet Remote connection

POWER SOURCE

- 100–240V AC, 50/60Hz, 50VA

OPERATING TEMPERATURE

- 0° to +40°C (32° to 104°F)

STORAGE TEMPERATURE

- -40° to +70°C (-40° to 158°F)

HUMIDITY

- 10% to 90%, RH (non-condensing)

INCLUDED ACCESSORIES

- Rack ears, power cord

PRODUCT DIMENSION

- 19" x 7.20 x 1U (43.6cm x 18.30cm 4.36cm) W, D, H

PRODUCT WEIGHT

- 1.9kg (4.1lbs) approx

SHIPPING DIMENSION

- 55.00cm x 27.60cm x 10.70cm (21.65" x 10.87" x 4.21") W, D, H

SHIPPING WEIGHT

- 2.9kg (6.4lbs) approx