

Kramer VS-611DT 6x1/2 4K60 4x2x0 HDBaseT Extended Reach PoE Auto Switching HDMI Switch

INPUTS

- 6 HDMI connectors, 1 IR on a 3.5mm mini-jack

OUTPUTS

- 1 HDMI connector, 1 HDBaseT on an RJ-45 connector, 1 balanced stereo audio on a 5-pin terminal block

PORTS

- 1 Ethernet on an RJ-45 connector, 1 RS-232 connector on a 3-pin terminal block, 6 contact closures on a 7-pin terminal block, 1 USB mini-A connector for firmware upgrading

MAX. DATA RATE

- 8.91Gbps (2.97Gbps per graphic channel) with 4K@60Hz (4:2:0) support

COMPLIANCE WITH HDMI STANDARD

- Deep Color, Ethernet, ARC, up to 7.1 Audio Channels, CEC

OUTPUT RESOLUTIONS

- Up to UXGA, 4K x 2K, 4K @60 4:2:0

CONTROL

- Local: front panel keyboard, contact closure, HDBaseT
- local and over HDBaseT: RS-232, Ethernet

SOFTWARE SUPPORT

- Protocol 3000, K Router Plus, EDID Designer, K-Upload

OPERATING TEMPERATURE

- 0° to +40°C (32° to 104°F)

STORAGE TEMPERATURE

- -40° to +70°C (-40° to 158°F)

HUMIDITY

- 10% to 90%, RHL non-condensing

POWER CONSUMPTION

- 12V DC, 750mA

INCLUDED ACCESSORIES

- Power cord, rack "ears"

OPTIONS

- RK-1 19" rack adapter

PRODUCT DIMENSION

- 21.46cm x 16.30cm x 4.36cm (8.45" x 6.42" x 1.72") W, D, H

PRODUCT WEIGHT

- 1.0kg (2.1lbs) approx

SHIPPING DIMENSION

- 35.10cm x 21.20cm x 7.20cm (13.82" x 8.35" x 2.83") W, D, H

SHIPPING WEIGHT

- 1.6kg (3.5lbs) approx