

Kramer VS-62DT 6x2 4K/60 4x2x0 HDMI/HDBaseT Long-Reach PoE Matrix Switcher

INPUTS

- 6 HDMI connectors

OUTPUTS

- 1 HDMI connector, 1 HDBT on an RJ-45 connector

PORTS

- 1 Ethernet on an RJ-45 connector, 12 remote selection contact-closure switches on 13 terminal block pins, 1 serial port on a 3-pin terminal block, 1 program port on a mini USB

ANALOG AUDIO

- 2 balanced stereo audio on 5-pin terminal blocks

BANDWIDTH

- Up to 8.91Gbps data rate (2.97Gbps per graphic channel)

COMPLIANCE WITH HDMI STANDARD

- HDMI 1.4 and HDCP 1.4

RESOLUTION

- Up to 4K@60Hz UHD (4:2:0)

SUPPORTED BAUD RATES

- 9600, 115200bps

POWER CONSUMPTION

- 48V DC 360mA
- 48V DC, 360mA

CONTROLS

- Front panel buttons, infrared remote control transmitter, RS 232, Ethernet, remote input selection switches and LEDS, built-in Web browser

OPERATING TEMPERATURE

- 0° to +40°C (32° to 104°F)

LED INDICATORS

- IR active — red, ON — green

STORAGE TEMPERATURE

- -40° to +70°C (-40° to 158°F)

HUMIDITY

- 10% to 90%, RHL non-condensing

INCLUDED ACCESSORIES

- Power supply, IR remote control

OPTIONS

- RK-1 19” rack adapter

PRODUCT DIMENSION

- 21.46cm x 16.30cm x 4.36cm (8.45" x 6.42" x 1.72") W, D, H

PRODUCT WEIGHT

- 1.0kg (2.3lbs) approx

SHIPPING DIMENSION

- 35.10cm x 21.20cm x 7.20cm (13.82" x 8.35" x 2.83") W, D, H

SHIPPING WEIGHT

- 1.7kg (3.7lbs) approx