

Barco R9023275 F35 WQXGA 7650 lumens High Brightness (MKIII) X-PORT Projector/No lens

| Image Display | |
|------------------------|---|
| Display System | Not Specified by Manufacturer |
| Native Resolution | 2560 x 1600 (WQXGA) |
| Supported Resolutions | WQXGA |
| Max Brightness | 7650 Lumens |
| Uniformity | Not Specified by Manufacturer |
| Offset | Not Specified by Manufacturer |
| Aspect Ratio | Native: 16:10 |
| Contrast Ratio | 8000:1 |
| Dynamic Contrast Ratio | Not Specified by Manufacturer |
| DLP Link 3D | Yes |
| Supported 3D Formats | Not Specified by Manufacturer |
| Scan | Horizontal: 10 - 150 kHz Vertical: 48 - 190 Hz |

| Input/Output Connectors | |
|--------------------------------|---|
| Inputs/Outputs | 2 x DVI-I Video (Input) 2 x HDMI Video (Input) 2 x VGA (DE-15) Video (Input) 1 x S-Video (4-Pin DIN) Video (Input) 1 x RS-232C (Unspecified Connector) Control (Input) 2 x 12 V Trigger Control (Input) 1 x 1/8" (3.5 mm) Mini Control (Input) 2 x USB Control (Input) |
| Wireless LAN | Not Specified by Manufacturer |

| General | |
|------------------------|---|
| Light Source | Not Specified by Manufacturer |
| Color Temperature | Not Specified by Manufacturer |
| Lamp Power | 300 W |
| Expected Lamp Life | Medium Brightness: 2000 Hours Low Brightness: 2500 Hours |
| Fan Noise | Not Specified by Manufacturer |
| Security | Not Specified by Manufacturer |
| Menu Languages | Not Specified by Manufacturer |
| Heat Dissipation | Not Specified by Manufacturer |
| Power Consumption | Full Brightness: 815 W |
| Max Operating Altitude | Not Specified by Manufacturer |
| Temperature | Operating 50 to 104°F (10 to 40°C) Humidity: 20 - 80% Storage -4 to 140°F (-20 to 60°C) Humidity: 10 - 90% |
| Dimensions (W x H x D) | 20.1 x 8.8 x 14.8" / 510.0 x 223.0 x 376.0 mm |
| Weight | 28.0 lb / 12.7 kg |