

Kramer VS-62HA 6x2 4K UHD HDMI/Audio Automatic Matrix Switcher

INPUTS:	6 HDMI connectors, 4 unbalanced stereo audio on 3.5mm mini jacks, 2 balanced stereo audio on 5-pin terminal blocks,
OUTPUTS:	2 HDMI connectors, 2 balanced stereo audio on 5-pin terminal blocks
PORTS:	1 RS-232 on a 3-pin terminal block, 1 Ethernet on an RJ-45 connector, 1 USB Type-C, 1 remote IR on a 3.5mm mini jack, 2x6 remote LED outputs on terminal blocks, 2x6 remote contact closure switches on terminal blocks
CONTROLS:	Front panel buttons, infrared remote control transmitter, RS-232, Ethernet, remote input selection switches and LEDs, built-in Web browser
LED INDICATORS:	IR active - red, ON - green
MAX. DATA RATE:	Up to 8.91 Gbps data rate (2.97Gbps per graphic channel)
COMPLIANCE WITH HDMI STANDARD:	HDMI and HDCP
RESOLUTION:	Up to 4K@60Hz UHD (4:2:0)
SUPPORTED BAUD RATES:	9600, 115200bps
SUPPORTED WEB BROWSERS:	<p>The following operating systems and Web browsers are supported:</p> <ul style="list-style-type: none">• Windows 7:<ul style="list-style-type: none">◦ Google Chrome v25◦ FireFox v15◦ Opera v12◦ Microsoft Internet Explorer v9• Windows XP:<ul style="list-style-type: none">◦ Google Chrome v25◦ FireFox v15• Apple Mac:<ul style="list-style-type: none">◦ Google Chrome v25◦ FireFox v20◦ Opera v12.14◦ Safari v6
POWER CONSUMPTION:	100-240V AC, 22VA
OPERATING TEMPERATURE:	0° to +40°C (32° to104°F)
STORAGE TEMPERATURE:	-40° to +70°C (-40° to158°F)
HUMIDITY:	10% to 90%, RHL non-condensing
DIMENSIONS:	43.6cm x 18.3cm x 4.36cm (17.2" x 7.2" x 1.7") W, D, H
WEIGHT:	1.65kg (3.63lb)
SHIPPING DIMENSIONS:	55cm x 27.6cm x 10.7cm (21.7" x 10.9" x 4.2") W, D, H
SHIPPING WEIGHT:	2.5kg (5.5lb)
INCLUDED ACCESSORIES:	Power cord, rack "ears"
OPTIONAL:	External remote IR receiver cable