

Aten CS1188DP 8-Port USB DisplayPort Secure KVM Switch (PSS PP v3.0 Compliant)

| | |
|------------------------------|---|
| Computer Connections | 8 |
| Port Selection | Pushbutton |
| Connectors | |
| Console Ports | 2 x USB Type-A Female (White) 1 x 6-pin Mini-DIN Female (Purple) 1 x 6-pin Mini-DIN Female (Green) 1 x HDMI Female (Black) 1 x Mini Stereo Jack Female (Green; front panel) |
| KVM Ports | 16 x USB Type-B Female (White) 8 x DisplayPort Female (Black) 8 x Mini Stereo Jack Female (Green) |
| Power | 1 x 3-prong AC Socket |
| USB CAC Port | 1 x USB Type-A Female (White; front panel) |
| Switches | |
| Port Selection | 8 x Pushbuttons |
| Reset | 1 x Semi-recessed Pushbutton |
| Power | 1 x Rocker |
| LEDs | |
| Power | 1 (Blue) |
| On Line/Selected (KVM Port) | 8 (Orange) |
| Online / Selected (CAC Port) | 8 (Green) |
| Video | 1 (Green) |
| Key Lock | 3 (Green) |
| Emulation | |
| Keyboard / Mouse | USB |
| Video | Max. 3840 x 2160 @ 30 Hz (UHD) |
| Maximum Input Power Rating | 100~240V~; 50-60 Hz; 1A |
| Power Consumption | AC110V:9.4WBTU AC220V:10WBTU |
| Environmental | |
| Operating Temperature | 0-50°C |
| Storage Temperature | -20-60°C |
| Humidity | 0 - 80% RH, Non-condensing |
| Physical Properties | |
| Housing | Metal |
| Weight | 3.30 kg (7.27 lb) |
| Dimensions (L x W x H) | 43.24 x 20.49 x 6.55 cm (17.02 x 8.07 x 2.58 in.) |
| Note | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format. |