

Aten CS1184D 4-Port USB DVI Secure KVM Switch (PSS PP v3.0 Compliant)

|                              |  |
|------------------------------|--|
| Computer Connections         | 4  |
| Port Selection               | Pushbutton   |
| Connectors                   |  |
| Console Ports                | 2 x USB Type-A Female (White)<br>1 x 6-pin Mini-DIN Female (Purple)<br>1 x 6-pin Mini-DIN Female (Green)<br>1 x DVI-I Dual Link Female (White)<br>1 x Mini Stereo Jack Female (Green; front panel) |
| KVM Ports                    | 8 x USB Type-B Female (White)<br>4 x DVI-I Dual Link Female (White)<br>4 x Mini Stereo Jack Female (Green)   |
| Power                        | 1 x 3-prong AC Socket  |
| USB CAC Port                 | 1 x USB Type-A Female (White; front panel)   |
| Switches                     |  |
| Port Selection               | 4 x Pushbuttons  |
| Reset                        | 1 x Semi-recessed Pushbutton   |
| Power                        | 1 x Rocker   |
| LEDs                         |  |
| Power                        | 1 (Blue)   |
| On Line/Selected (KVM Port)  | 4 (Orange)   |
| Online / Selected (CAC Port) | 4 (Green)  |
| Video                        | 1 (Green)  |
| Key Lock                     | 3 (Green)  |
| Emulation                    |  |
| Keyboard / Mouse             | USB  |
| Video                        | 3840x2160@30Hz*; DVI Dual Link: 2560x1600;<br>DVI Single Link: 1920x1200<br>DVI-A: 2048x1536   |
| Maximum Input Power Rating   | 100~240V~; 50-60 Hz; 1A  |
| Power Consumption            | AC110V:5.4W:45BTU<br>AC220V:5.4W:45BTU   |
| Environmental                |  |
| Operating Temperature        | 0-50°C   |
| Storage Temperature          | -20-60°C   |
| Humidity                     | 0 - 80% RH, Non-condensing   |
| Physical Properties          |  |
| Housing                      | Metal  |
| Weight                       | 1.80 kg ( 3.96 lb )  |
| Dimensions (L x W x H)       | 33.50 x 16.43 x 4.40 cm<br>(13.19 x 6.47 x 1.73 in.)   |
| Note                         | * DVI Secure KVM Switches offer 3840 x 2160 @ 30 Hz video output on compatible HDMI-interfaced monitors/computers with ATEN DVI-to-HDMI KVM cables.  |
| Note                         | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.  |