

# Kramer VS-622DT All-in-One Presentation System with 6x2 4K60 4x2x0 HDMI/HDBaseT Matrix Switching/Control Gateway/PoE

## INPUTS

- 2 HDBT with PoE: On female RJ-45 Connectors
- 4 HDMI: On female HDMI connectors

## OUTPUTS

- 1 HDBT with PoE: On a female RJ-45 Connector
- 1 HDMI: On a female HDMI connector
- 2 Stereo Balanced Audio: On 5-pin terminal block connectors
- 1 Power Amplifier for Stereo or 1 Mono Speaker: On a 4-pin large terminal block

## PORTS

- 1 Ethernet: On an RJ-45 female connector
- 2 RS-232: On 3-pin terminal blocks
- 1 USB (PROG): On a mini USB connector, for firmware upgrade
- 4 IR: On 2-pin terminal block connectors
- 2 GPI/O: On 2-pin terminal block connectors
- 2 Relays: On 2-pin terminal block connectors

## VIDEO

- Max Resolution: Up to 4K@60Hz UHD (4:2:0)
- Compliance: HDMI 1.4 and HDCP 1.4

## POWER AMPLIFIER

- 1 x 120W @ 70V/100V
- 2 x 60W @ 4/8Ω

## EXTENSION LINE

- Up to 100m (330ft): At 4K@60Hz (4:2:0)
- Up to 130m (430ft): At Full HD (1080p @60Hz 36bpp)
- Up to 180m (590ft): HDBaseT Ultra Mode and Full HD (1080p @60Hz 24bpp)

## USER INTERFACE

- Controls: Input selection buttons, swap, EDID, lock and audio control buttons
- Indicators: Power, RS-232, IR, GPI/O and relay LEDs
- Remote: RS-232, Ethernet, Web pages, IR remote control transmitter, Programmable Maestro buttons interface

## POWER

- Source: 100-240V AC
- Consumption: 250VA max

## ENVIRONMENTAL CONDITIONS

- Operating Temperature: 0° to +40°C (32° to 104°F)
- Storage Temperature: -40° to +70°C (-40° to 158°F)
- Humidity: 10% to 90%, RHL non-condensing

## REGULATORY

- Safety: CE
- Environmental: RoHs, WEEE

## ENCLOSURE

- Size: 19", 1U
- Type: Aluminum
- Cooling: Fan Ventilation

## ACCESSORIES

- Included: Power cord

## PRODUCT DIMENSION

- 43.64cm x 23.72cm x 4.36cm (17.18" x 9.34" x 1.72" ) W, D, H

**PRODUCT WEIGHT**

- 2.6kg (5.7lbs) approx.

**SHIPPING DIMENSION**

- 52.50cm x 33.00cm x 10.70cm (20.67" x 12.99" x 4.21" ) W, D, H

**SHIPPING WEIGHT**

- 3.7kg (8.2lbs) approx.