

Hall Technologies KVM-HDU-4 4-Port HDMI KVM Switch with USB 2.0 Hub and 4K (UHD) Resolution Support

| | |
|-------------------------|--|
| Video Standard: | HDMI |
| Number of Inputs: | 4 |
| Bandwidth: | 300 MHz pixel clock or 10.2 Gbps video data rate |
| Max Resolution: | 3840 x 2160 @ 60Hz (with 4:2:0 YUV color sampling) 3840 x 2160 @ 30Hz (with 4:4:4 YUV color sampling) |
| USB Standard: | Version 2.0 |
| Connectors: | 4x USB Type A Female for Hosts (PCs) 1x Keyboard Type A Female 1x Mouse Type A Female 2x USB 2.0 Peripherals from Built in Hub. Type A Female |
| Optional Power Supply: | 2 VDC@ 2A Note: Power supply is not needed if USB inputs are connected |
| Power Consumption: | 0.7 watts Excluding extra power drawn by USB devices that may be connected |
| Temperature / Humidity: | Storage: -40 to +158 °F (-40 to +70 °C) /10% to 90%, non-condensing Operating: +32 to +122 °F (0 to +50 °C) /10% to 90%, non-condensing |
| Cooling: | Convection |
| Enclosure type: | Metal |
| Dimensions: | 9.65" x 3.74" x 1.61" (245mm x 95mm x 41mm) |
| Vibration: | ISTA 1A in carton (International Safe Transit Association) |
| Safety: | CE |
| EMI/EMC: | CE, FCC Class A |
| MTBF: | 90,000 hours (Calculated Estimate) |
| Warranty: | 3 years parts and labor |