

Kramer FC-174 4 Channel HDMI 4K60 Converter with HDCP 1.4 and 2.2

INPUTS

- 4 HDMI: On female HDMI connectors

OUTPUTS

- 4 HDMI: On female HDMI connectors

PORTS

- 1 USB: On a female USB type-A connector for firmware upgrade
- 1 RS-232: On a 9-pin D-sub connector for EDID management via a software application

VIDEO

- HDMI Standards Compliance: 1.4 & 2.0
- HDCP Standards Compliance: 1.4 & 2.2
- Max. Resolution: 4K@60Hz (4:4:4)

USER INTERFACE

- Control: OSD menu via front panel buttons
- Indicators: ON LED

POWER

- Source: 5V DC
- Consumption: 1.8A

ENVIRONMENTAL CONDITIONS

- Operating Temperature: 0° to +40°C (32° to 104°F)
- Storage Temperature: -40° to +70°C (-40° to 158°F)
- Humidity: 10% to 90%, RHL non-condensing

ACCESSORIES

- Included: Power adapter, bracket set
- Optional: RK-T2B 19" rack adapter

PRODUCT DIMENSION

- 18.75cm x 11.50cm x 2.54cm (7.38" x 4.53" x 1.00") W, D, H

PRODUCT WEIGHT

- 0.5kg (1.0lbs) approx.

SHIPPING DIMENSION

- 34.50cm x 16.50cm x 5.20cm (13.58" x 6.50" x 2.05") W, D, H

SHIPPING WEIGHT

- 1.0kg (2.2lbs) approx.