

Kramer VS-21T 2x1 Selector for Ethernet and HDBaseT Signals

INPUTS

- 2 HDBaseT Signal / Ethernet: On RJ-45 connectors

OUTPUTS

- 1 HDBaseT Signal / Ethernet: On an RJ-45 connector

VIDEO

- Max. Data Rate: 8.91Gbps (2.97Gbps per graphic channel) pass-through
- Max. Resolution: 4K@60Hz (4:2:0) pass-through
- Standards Compliance: HDCP 2.2

USER INTERFACE

- Controls: Contact closure connectors for remote control switches
- Indicators: Active input and ON

POWER

- Source: 5V DC
- Consumption: 30mA

ENVIRONMENTAL CONDITIONS

- Operating Temperature: 0° to +40°C (32° to 104°F)
- Storage Temperature: -40° to +70°C (-40° to 158°F)
- Humidity: 10% to 90%, RHL non-condensing

PRODUCT DIMENSION

- 12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H

PRODUCT WEIGHT

- 0.2kg (0.5lbs) approx.

SHIPPING DIMENSION

- 15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H

SHIPPING WEIGHT

- 0.7kg (1.5lbs) approx.