

TASCAM TM-DRUMS Four-Microphone Kit for Drum Recording/50Hz -15000Hz

TM-50DB

- Model:
Dynamic
- Directivity:
Cardioid (unidirectional)■
- Frequency response:
50Hz -15,000Hz
- Output impedance:
400Ω +/-30% (at 1 kHz)
- Load impedance:
<1kΩ
- Sensitivity:
-55dB +/-3dB (0dB=1V/Pa at 1kHz)
- Connector:
3 pin XLR, Male
- External dimensions:
59(W) . 118 (H) . 115 (D) mm/ 2.32 x 4.65 x 4.53 inch
- Weight:
460g (Microphone body only)
- Included Accessories:
5/8 inch -3/8 inch conversion adapter

TM-50DS

- Model:
Dynamic
- Directivity:
Cardioid (unidirectional)■
- Frequency response:
50Hz -14,000Hz
- Output impedance:
350Ω +/-30% (at 1kHz)
- Load impedance:
<1kΩ
- Sensitivity:
-56dB +/-3dB (0dB=1V/Pa at 1kHz)
- Connector:
3 pin XLR, Male
- External dimensions:
42.5(W) . 105 (H) . 98 (D) mm/ 1.67 x 4.13 x 3.86 inch
- Weight:
330g (Microphone body only)
- Accessories:
5/8 inch -3/8 inch conversion adapter

TM-50C

- Model:
Condenser (16mm diaphragm)
- Directivity:
Cardioid (unidirectional)
- Frequency characteristics:
30Hz -18,000Hz
- Output impedance:
100Ω +/-30% (at 1kHz)
- Load impedance:
<1kΩ
- Sensitivity:
-38dB +/-3dB (0dB=1V/Pa at 1kHz)
- Maximum SPL:
130dB

- Signal-noise ratio:
74dB
- Connector:
3 pin XLR, Male
- External dimensions:
21(W) . 117 (H) . 21 (D) mm/ 0.83 x 4.61 x 0.83 inch
- Weight:
85g (Microphone body only)
- Included Accessories:
Microphone holder, 5/8 inch -3/8 inch conversion adapter