

# TASCAM CD-200BT Professional Single CD Player with Bluetooth/AptX Codec

<b>Playback media</b>	CD,CD-R,CD-RW (8/12cm)
<b>Playback format</b>	
<b>CD-DA</b>	Stereo, 44.1kHz, 16bit
<b>WAV(Data CD)</b>	Stereo, 8/16/32/11.025/22.05/44.1/12/24/48kHz, 16bit
<b>MP2(Data CD)</b>	Stereo, 32/44.1/48kHz■32-384kbps
<b>MP3(Data CD)</b>	Stereo, 32/44.1/48kHz■32-320kbps, VBR
<b>Analog audio input</b>	
<b>AUX</b>	
Connector	1/8"(3.5mm) Stereo Mini Jack
Input impedance	22k ohms
Nominal input level	-20dBV
Maximum input level	-4dBV
<b>Analog audio output</b>	
<b>UNBALANCED</b>	
Connector	RCA pin-jack
Output impedance	200 ohms
Nominal output level	-10dBV(0.32Vms)
Maximum output level	+6dBV(2.0Vms)
<b>Digital audio output</b>	
<b>COAXIAL</b>	
Connector	RCA pin-jack
■Format	IEC60958-3(S/PDIF)
<b>OPTICAL</b>	
Connector	TOS(JEITA RC-5720C)
Format	IEC60958-3(S/PDIF)
Bluetooth®	
Version	3.0
Output Class	Class 2
Supported profile	A2DP■AVRCP
Supported A2DP codec	SBC■AAC■aptX®
Supported contents protection	SCMS-T
<b>PHONES</b>	
Connector	6.3mm(1/4") stereo phone jack
Maximum output level	20mW + 20mW (THD 0.1%, 32ohms loaded)
<b>Power</b>	AC120V, 60Hz (North American)/AC230V, 50Hz (EUR)/AC240V, 50Hz (Australia)
<b>Power consumption</b>	11W
<b>Dimensions</b>	481(W)×94.5(H)×298(D)mm
<b>Weight</b>	4.5kg
<b>Operating temperature</b>	5-35■C
<b>Inclination of installation</b>	5■ or less
Standard accessories	Wireless remote controller(RC-CD200BT), AA battery, Rack mounting screw kit, Warranty card, Owner's manual

<b>Audio performance</b>	
<b>Frequency response</b>	20Hz-20kHz, +/-1dB(playback, JEITA)
<b>Distortion</b>	0.01% or less(playback, JEITA)
<b>S/N ratio</b>	90dB or greater(playback, JEITA)

<b>Dynamic range</b>	90dB or greater(playback, JEITA)
<b>Channel separation</b>	90dB or greater(playback, JEITA)