

TASCAM DA-6400dp Compact 64-channel digital multitrack recorder/player with Redundant Power Supply

Recording media	SSD Note: HDD support also planned in addition to the SSD.
File system	FAT32
File formats	BWF(.wav)
Number of channels	64(1xFs), 32(2xFs)
Sampling frequencies	44.1k/48k/88.2k/96kHz
Quantization bit rate	16bit/24bit
Clock reference	INTERNAL, WORD IN, VIDEO IN
Timecode frame	23.976 / 24 / 25 / 29.97DF / 29.97NDF / 30DF / 30NDF
TIME CODE IN	
Connector	BNC
Signal voltage amplitude	0.5V to 5Vp-p
Input impedance	10k Ω
Format	SMPTE 12M-1999 compliant
TIME CODE OUT	
Connector	BNC
Signal voltage amplitude	2Vp-p
Output impedance	600 Ω
Format	SMPTE 12M-1999 compliant
WORD/VIDEO IN	
Connector	BNC
Input voltage amplitude (WORD)	0.5V to 5Vp-p TTL equivalent
Signal voltage amplitude (VIDEO)	1Vp-p
Input impedance	75 Ω +/-10%
Input frequency (WORD)	48kHz
Input signal (VIDEO)	23.976/24/25/29.97/30 Frame (NTSC/PAL Black burst, HDTV Tri-Level)
WORD/VIDEO THRU/OUT	
Connector	BNC
Output voltage amplitude	5V TTL equivalent
Output frequency (WORD)	48kHz
ETHERNET	
Connector	RJ-45
Protocol	100BASE-TX, 1000BASE-T
RS-422	
Connector	D-sub 9 pin (female, inch-standard)
PARALLEL	
Connector	D-sub 15 pin (female, inch-standard)
USB	
Connector	USB2.0 A-type
Protocol	USB 2.0 HIGH SPEED(480Mbps)
PHONES	
Connector	6.3mm(1/4") standard stereo jack
Maximum output level	45mW+45mW or higher
Power	AC100V-240V, 50/60Hz *DA-6400dp has 2 power supply inlets
Power consumption	21W (At the time of IF-MA64/EX use)

Dimensions	482.6(W)×44.7(H)×304.8(D)mm
Weight	
DA-6400	3.9kg
DA-6400dp	4.0kg
Operating temperature	0 to +40■C
Standard accessories	TASCAM SSD, SSD media case, Power cable×1 (DA-6400), Power cable×2 (DA-6400dp), USB cable, Rack mount screw kit, Security screw kit, Owner's manual (with warranty)