

Patton CL1101E/PAFA/RJ45/EUI-2PK Industrial CopperLink PoE Extender (Local/Remote) Kit/RJ45/Line Powered

| | |
|----------------------------|--|
| Line Interfaces (Data) | 1 x RJ45 (Optional: Terminal Block, Coax) Supports 1-4 pairs |
| Ethernet Interfaces | 1 x RJ45 Auto-Sensing 10/100Base-TX with full or half-duplex operation |
| LEDs | Power, Line, (10 or 100 operation), Eth, and PoE |
| Protocol | Transparent to high layer protocol Supports 802.1Q VLAN tagged frames Transparent to IP video schemes Fully transparent to compression schemes such as WMV, MPEG-4, and MJPEG |
| Power Injection (PSE only) | DC voltage on Ethernet port 54 VDC |
| Power Consumption | 1.5 W |
| Power Supply | External AC Adapter 100-240 VAC to 54 VDC Input: 30-57 VDC (Recommended 54 VDC) |
| MTBF | 83,043 hours |
| Environment | Temperature: 0 to 50°C (standard) Humidity: 10 to 95% (non-condensing) |
| Physical | 0.71 H x 1.1 W x 2.56 D in. (18 H x 28 W x 65 D mm) 0.78 oz (22 g) |
| Compliance | FCC Part 15A, Class B CE Mark EMC Directive 89/336/EEC LVD Directive 73/23/EEC |