

Patton CL2304/4ETH/EUI-2PK CopperLink 2-8 Wire Ethernet Extender (Local/Remote) Kit/4 Eth/100-240VAC

CopperLink	Line Interface: RJ45 TC-PAM line modulation 16/32 and 64/128 Configurable as either remote or local Rate negotiating/manually rate adaptation configuration 2 to 8-wire mode auto-detect Data rate selections: Up to N x 239 (5.7 Mbps) per pair
Ethernet Interface (x3) + PoE (Optional)	3x Auto-sensing 10/100 w/half or full duplex operation 1 port 802.3af, PoE 13 Watts
USB 2.0 Interface (Optional)	USB 2.0 interface (optional) Coming soon!
Ethernet Protocols	Transparent bridging (IEEE 802.1D) VLAN based QOS (802.1P/Q) ARP DHCP Client/Server DNS Server/Relay
Management	HTTP NTP SNMPv1,v2 SYSLOG Client CLI (Telnet, SSH, Console Port) TFTP-Firmware upgrade, import/export config
Monitoring	8 LEDs: Power, Link, Ethernet 1-4, Remote, Local
Power Supply	External AC:100 to 240 VAC or DC: -48, -24, or -12 VDC
Compliance	FCC Part 15A, CE Mark, EMC Directive 89/336/EEC, Low-Voltage Directive 73/23/EEC
Environment	Temperature: 0 to 50°C; Humidity: 5 to 95%, non-condensing Extended Temperature -40 to 85C available
Dimensions	7.3 x 6.6 x 1.62 in. (185 x 168 x 41 mm)
Weight	0.4 lbs (181 g)