

A-NeuVideo ANI-2PIP-LOGO 2x1 HDMI Dynamic Multiviewer PiP/PoP with Logo Inserter

- **HDMI Bandwidth:** 225MHz/6.75Gbps
- **Input Ports:** (2) HDMI
- **Output Ports:** (1) HDMI / (1) Stereo (Terminal Block)
- **Control Interfaces:**
 - (8) Trigger (Terminal Block)
 - RS-232 (9-pin D-sub)
 - IP Control (RJ-45)
- **Baud Rate:** Up to 115200bps
- **Power Supply:** 5V/2.6A DC (US/EU standards, CE/FCC/UL certified)
- **ESD Protection:** Human Body Model:
 - ±8 kV (air-gap discharge)
 - ±6 kV (contact discharge)
- **Dimensions (WxHxD):** 9.1 x 1 x 4.25 in (231.5x25x108mm) [Case Only] 9.1 x 1 x 4.7 in (231.5x25x116mm) [All Inclusive]
- **Weight:** 1.4 lb/652g
- **Chassis Material:** Metal
- **Silkscreen Color:** Black
- **Operating Temperature:** 0°C-40°C/32°F-104°F
- **Storage Temperature:** -20°C-60°C/-4°F-140°F
- **Relative Humidity:** 20-90% RH (Non-condensing)
- **Power Consumption:** 5.1W