

AVPro Edge AC-MX88-UHD-GEN2 HDMI UHD 8x8 Matrix Switch

HDMI Inputs	8
HDMI Outputs	8
HDMI Output Format	1.4 and 2.0
Video formats supported	4K60 (4:2:0), 4K30, 1080p, 1080i, 720P, 576P, 480P, 576i, 480i
Audio formats supported (HDMI)	Up to DTS-HD, Dolby trueHD
SPDIF Audio Outputs	8
Audio Formats Supported (SPDIF)	Up to Dolby 5.1 PCM
HDCP VERSIONS	2.2 and earlier
Signal rate	10.2 Gbps
Input Video Signal	0.5-1.0 volts p-p
Input DDC Signal	5 volts p-p
Transmission Distance over HDMI	45 Feet (15 Meters)
Control	RS-232, IR, Ethernet
RS-232 Settings	Baud rate: 57600 Data bits: 8 Parity: None Stop Bits: 1 Handshaking: None
Power Supply	12V 3A
Power Consumption	30W (Max)
Operating Temperature	32-95°F (0-35°C)
Operating Humidity	15-90% RH
Weight	5.3LBS
Dimensions	L440 x W256 x H42 mm 17.3 x 10 x 1.65 in 19 inch RU's: 1