

Electro-Voice ETX12PUS Performance High Power active 12 inch 2 way speaker/2000W/43Hz-20kHz

Weight Net	23.6kg (52.03 lbs)
Depth	400mm (15.75")
Width	381mm (15")
Height	613mm (24.13")
Connector Type	(2) XLR/TRS combo jack and (1) XLR link output
Coverage (Nominal -6 dB) H	90°
Coverage (Nominal -6 dB) V	60°
Crossover Frequency	1600Hz
Enclosure Material	18-mm, 13-ply birch plywood with EVCoat
Family	ETX
Frequency Range (-10 dB)	43 Hz - 20 kHz
Frequency Response (-3 dB)	55 Hz - 20 kHz
Grille	16AWG steel with powdercoat
HF Transducer	DH3-B 1.25-in titanium compression driver
LF Transducer	SMX2120 300 mm (12 in)
Max. SPL/1m (calc)	135dB
Maximum SPL	135 peakdB
Power Consumption	100 - 240 V~, 50 - 60 Hz, 1.6 - 0.8 A
Power Rating	2000W
Powered or Passive	Powered
Shipping Weight	26.8kg (59.08 lbs)
Speaker Type	Full-Range, two-way
Suspension	(8) M10 suspension points
Woofers Size	12inch