

Adder X2-DA-GOLD/P-US Dual Access KVM Extender (Transmitter/Receiver) over Cat6 with Audio/RS232 up to 300m

Video resolutions

1900x1400 at distances up to 50m (150ft), 1600x1200 at distances up to 200m (650ft), 1280x1024 at distances up to 300m (1000ft)

Extension distance

Up to 300 metres/1000ft using CATx cable (x=5,5e,6,7)

Devices supported

Supports PS/2 style keyboard, PS/2 style mouse, flat-screen and CRT style monitors with standard HD-15 video connectors. Transparent RS232 connection.

O/S compatibility

All known software and operating systems including Windows (all), DOS, Linux, Unix, BSD, Sun OS, Solaris, Mac OS, NetWare etc.

Connectors (Local computer-end unit)

Computer connection: 1 x 25-way female connector (cable supplied). Local console connection (DA only) video HDD15, keyboard/mouse: MiniDin6. Audio: 1x light green 3.5mm audio jack. CATx: 1 x RJ45 connector. Serial: DB9. Optional power: 2.5mm DC jack.

Connectors (Remote console-end unit)

Video: HDD15 Keyboard/Mouse: MiniDin6. Audio: 1 x light green 3.5mm audio jack and 1 x pink 3.5mm audio jack. CATx: 1 x RJ45 connector. Serial: DB9. Power: 2.5mm DC jack.

Physical (Tx and Rx units)

172mm x 26mm x 75mm, 430g, fits into one slot width in the X-Series rack mount chassis (16 units fit into 2U of rack space)

Power supply

100-240VAC, 50-60Hz

Operating temperature

0 - 40 deg C / 32 to 104 deg F

Approvals

CE, FCC