

**Electro-Voice PA1250T120V PA Series Amplifier (1x 270W/70V/2RU)**

|   |                    |
|---|--------------------|
| Weight Net  | 16.5kg (36.38 lbs) |
| Depth   | 406mm (15.98")     |
| Width   | 483mm (19.02")     |
| Height  | 88mm (3.46")       |
| Channels  | 1                  |
| Continuous Rated Power (1 kHz, THD 1%) 100v       | 270Watts           |
| Continuous Rated Power (1 kHz, THD 1%) 2Ω         | 270Watts           |
| Continuous Rated Power (1 kHz, THD 1%) 70v        | 270Watts           |
| Continuous Rated Power (20-20 kHz, THD<0,2%) 100v | 250Watts           |
| Continuous Rated Power (20-20 kHz, THD<0,2%) 70v  | 250Watts           |
| Crosstalk   | < < -75dB          |
| DIM 30  | < 0.1%             |
| Frequency Response (-3 dB)                        | 65Hz-20kHz         |
| Input Impedance (Balanced)                        | > 20kΩ             |
| Input Sensitivity                                 | 0 dBu              |
| Intermodulation Distortion (SMPTE)                | < 0.1%             |
| Network Control (IRIS-Net)                        | No                 |
| Number of Channels                                | 1                  |
| Signal-to-Noise Ratio (A-weighted)                | 103dB              |
| Slew Rate   | 41/61V/μs          |
| Total Harmonic Distortion                         | < 0.1%             |