

## Kramer 106 1x2 Microphone Line and Distribution Amplifier

<b>INPUT:</b>	1 balanced mono microphone on a 3-pin terminal block connector.
<b>OUTPUTS:</b>	2 balanced mono line outputs on 3-pin terminal block connectors.
<b>MAX. OUTPUT LEVEL:</b>	27Vpp (22dBu).
<b>BANDWIDTH:</b>	>40kHz.
<b>S/N RATIO:</b>	81dB.
<b>CONTROLS:</b>	Mic. type selector pushbutton, -14dB to +68dB LINE OUT trimmers (master trimmer at max.), +37dB to +68dB master trimmer (line out trimmer at max.)
<b>COUPLING:</b>	Input, AC; output, DC.
<b>AUDIO THD + NOISE:</b>	0.18%.
<b>AUDIO 2nd HARMONIC:</b>	0.16%.
<b>POWER SOURCE:</b>	12V DC, 132mA.
<b>DIMENSIONS:</b>	12cm x 7.5cm x 2.5cm (4.7" x 2.95" x 0.98") W, D, H.
<b>WEIGHT:</b>	0.3kg (0.66lbs) approx.
<b>ACCESSORIES:</b>	Power supply, mounting bracket
<b>OPTIONS:</b>	RK-3T 19" rack adapter.