

## A-NeuVideo ANI-28UHDDA 2x8 UHD 4K 60Hz HDR 18G HDMI Splitter Individual Output

- **HDMI Bandwidth:** 600MHz/18Gbps
- **Input Ports:** (2) HDMI
- **Output Ports:** (8) HDMI
- **Control Interfaces:** RS-232 [3-Pin Terminal Block] & USB [Mini-B]
- **HDMI Cable Distance:**
  - ~16 ft/5M, 4K@60Hz (YUV 4:4:4, 8-bit)
  - ~32 ft/10M, 1080p@60Hz (12-bit)
  - ~49 ft/15M, 1080p@60Hz (8-bit)
- **Power Supply:** 5V/3A DC (US/EU Standards, CE/FCC/UL Certified)
- **CAT Cable Distance:** ~985ft/300M
- **Power Supply:** 12VDC/1.25A (US/EU standards, CE/FCC/UL certified)
- **ESD Protection:** Human Body Model:
  - ±8 kV (air-gap discharge)
  - ±6 kV (contact discharge)
- **Dimensions (WxDxH):** 9.4 x 1 x 4 in (240x24x103mm)
- **Weight:** 1.4 lb/ 616g each
- **Chassis Material:** Metal
- **Silkscreen Color:** Black
- **Operating Temperature:** 0°C~40°C / 32°F~104°F
- **Storage Temperature:** -20°C~60°C / -4°F~140°F
- **Relative Humidity:** 20~90% RH (no condensation)
- **Power Consumption:** 9.57W