

ZyPerMX4

Quad-Channel H.264 HD Encoder

Designed to encode and deliver H.264 video up to 1080p, the ZyPerMX4 allows organizations to deliver content over any IP network. With four encoders in a single appliance, IT/AV managers can deliver more content while utilizing fewer network resources.

Flexible HD Encoding


ZyPerMX4 delivers compressed 720p and 1080p HD resolution content directly over a standard Ethernet network.

Multiple Transport and Playback Options

Receive content on a wide variety of devices, including televisions/displays, computers, and smart devices via unicast, multicast or HLS.

Effortless Deployment

The ZyPerMX4 supports power over Ethernet (POE) reducing the need for power supplies — all you need is an Ethernet switch that supports POE. Management is also a snap via web-based administration — providing full access to configuration parameters, control, and advanced features. Streams from the ZyPerMX4 are also auto-discovered by the ZvMXE+ set-top-box.



Highlights:

- 4 HDMI inputs
- H.264/MPEG-4 AVC and HLS encoding
- Supports up to 1080p
- Linear PCM input, MP2 or AC3 audio output
- Built-in web server for control and configuration
- Power over Ethernet (PoE) support

Models:

ZMXENC4-4

Includes up to 4 HLS streams per HDMI Input.

ZMXENC4-100

Includes up to 100 HLS streams per HDMI Input.

Maestro Administration Interface

5 connected **Manage All** Apply Reset IP Channel Help

Headend: Unnamed, No location Edit User Name: admin Logout Send Emergency Alert **Maestro™**

Status Channel Plan **IP Streaming** SSL AV Source Device Network STB EAS Config Admin Support About

At least one parameter has been changed. Click "Apply" to save your new settings.

System	Auto-name...	Slot	AV Port	Enabled	Transport	Stream IP	Stream Port	Prog #	Name	Encryption	High Bitrate	Low Bitrate	Low Resolution	Stream URL
1 selected					Set All	Set All	Set All	Set All	Set All	Set All	Set All	Set All	Set All	
MX4_ZyPer_Sources		1	1	Enabled	HLS	0.0.0.0	0	1	MYTV-1	disable	6	3	1080p30	http://192.168.4.11/media/MYTV-1.m3u8
		2	2	Enabled	HLS	0.0.0.0	0	2	MYTV-2	disable	6	3	1080p30	http://192.168.4.11/media/MYTV-2.m3u8
		3	3	Enabled	HLS	0.0.0.0	0	3	MYTV-1	disable	6	3	1080p30	http://192.168.4.12/media/MYTV-1.m3u8
		4	4	Enabled	HLS	0.0.0.0	0	4	MYTV-2	disable	6	3	1080p30	http://192.168.4.12/media/MYTV-2.m3u8

Show advanced controls Apply Reset IP Channel Help


At least one parameter has been changed. Click "Apply" to save your new settings.

Input		
Video	Connector	4 x HDMI Type A, female
Audio Formats	Linear PCM	
Closed Caption Audio		4 x 3.5mm jack
Output		
LAN	Connector	1 x RJ-45 (PoE), shielded
Audio Formats	MP2, AC3	
Format		
HDMI: 720 x 480p, 1280 x 720p, 1920 x 1080p		
Other Specifications		
Video Encoding (output)	H.264/MPEG-4 AVC, HLS	
Audio Encoding (output)	MP2, AC3	
Output Bit Rate	1 Mbps - 10 Mbps	
Power input (locking connector)	12 VDC 1A (Worldwide AC adapter is supplied)	
Dimensions (L x W x H)	7.09 in (180 mm) x 4.41 in (112 mm) x 1.34 in (34 mm)	
Temperature	Operating temperature: 32 to 104 °F [0 to +40 °C] Storage temperature: -4 to +176 °F [-20 to +80 °C]	
Humidity	Operating/ Storage humidity: 20% to 90% (non-condensing)	

ZyPerMX4 Front View



ZyPerMX4 Rear View



ZeeVee, Inc., headquartered in Littleton, Mass., and founded in 2007, is a leading global developer of digital technology and products for distributing audio-video content from any source or multiple sources to any number of displays. Manufactured in the U.S. and used primarily in commercial and corporate applications, ZeeVee products are employed worldwide by major organizations in education, government, hospitality, retail, sports, entertainment, broadcasting, healthcare, housing, energy and other industries. For more information visit www.zeevee.com