

Electro-Voice SX600PI Sx Series Dual 12 inch 600W RMS/2400W Peak 2-Way Speaker (Black/Weatherized)

Frequency Range (-10 dB)	70 - 16000kHz
Weight Net	36.3kg (80.03 lbs)
Depth	312mm (12.28")
Width	429mm (16.89")
Height	1163mm (45.79")
Available Color	Black
Axial Sensitivity (SPL, 1 W @ 1 m)	105dB
Chassis Size	304.8 mm
Coverage (Nominal -6 dB) H	65°
Coverage (Nominal -6 dB) V	65°
Crossover Frequency	1800Hz
Directivity Index	11.3dB
Enclosure Material	High Density Polymer
Family	Sx
Flying	Yes
HF Transducer	2-inch DH2T
Input Connections	SJO cable/gland nut
Internal Crossover	Yes
LF Transducer	One 12-inch DL12BFH (LF), one 12-inch ND12 (MB)
Max. SPL/1m (calc)	139dB
MF Transducer	ND12A
Minimum Impedance	3.5Ω
Nominal Impedance (Passive)	4Ω
Passive Power Handling	2400W peak
Power Rating	2400W
Recommended High-Pass Frequency	90 @Q=1.6Hz
Sensitivity 1 W/1 m	105dB
Speaker Type	Full-Range, Two-Way
System Power Handling (Continuous/Program/Peak)	600//2400Watts (Const.-dir. horn)
Weatherized	Yes