

Electro-Voice EVID4.2 EVID Series 200 Watt 2-Way Speaker (Black/Pair)

| | |
|------------------------------|--|
| Frequency Response 1(-10 dB) | 65Hz - 20kHz |
| Power Handling 2 | 200W Cont. Prog./400W Peak |
| Sensitivity 3 | 89 dB, 1W/1m |
| Impedance | 8 ohms |
| Max SPL | 113 db |
| Horizontal Coverage 4 | 120° |
| Vertical Coverage 4 | 80° |
| Crossover Frequency | 2.2 kHz |
| LF Transducer | 2 x 4" (100 mm) |
| HF Transducer | 1" (25 mm) |
| Protection | Full System |
| Weather Resistance | Meets Mil Spec 810 humidity, salt spray, temperature and UV, and IEC 529 IP 34 splashproof ratings |
| Swing x Rotation | 100° x 90° |
| Terminals | Phoenix Connector |
| Enclosure Material | ABS (paintable) |
| "t" Version Wattage Taps | 70V: 3.75 W 70V/100V: 7.5W, 15W, 30W, 8 ohm bypass |
| Dim (H x W x D) | 12.2" x 6.9" x 8.5" (234 mm x 127 mm x 165 mm) |
| Net Weight (each) | 8.5 lbs (3.9 kg) |
| Shipping Weight (pair) | 19 lbs (8.6 kg) |
| Included Accessories | SAM™, hex key |

1. Half Space (wall mounting)
2. Continuous Program Rating: 3 dB greater than continuous pink noiserating (IEC-shaped pink noise with 6dB crest factor)
3. Avg: Half Space (wall mounting)
4. When mounted with long axis in vertical plane