

**Electro-Voice EVF1122D/99WHT Premium 12 inch 2-Way Full-Range Loudspeaker/90x90deg/Evcoat/White**

|                                                 |                                                                                                      |
|-------------------------------------------------|------------------------------------------------------------------------------------------------------|
| Frequency Range (-10 dB)                        | 49 - 21000kHz                                                                                        |
| Weight Net                                      | 29.7kg (65.48 lbs)                                                                                   |
| Depth                                           | 413.3mm (16.27")                                                                                     |
| Width                                           | 406.3mm (16")                                                                                        |
| Height                                          | 768.6mm (30.26")                                                                                     |
| Coverage (Nominal -6 dB) H                      | 90°                                                                                                  |
| Coverage (Nominal -6 dB) V                      | 90°                                                                                                  |
| Crossover Frequency                             | 1300Hz                                                                                               |
| Enclosure Material                              | 13-ply weather-resistant birch with EVCoat                                                           |
| Environmental Specs                             | Standard versions: IEC 60529 IP44, PI and FG versions: IEC 60529 IP55                                |
| Frequency Response (-3 dB)                      | 57 - 18000kHz                                                                                        |
| Grille                                          | 16 GA powder-coated galvalume with screen behind                                                     |
| HF Transducer                                   | DH7N 3-inch (76mm) diaphragm compression driver                                                      |
| Input Connections                               | Phoenix/Euroblock style screw terminals; PI and FG versions include dual-gland-nut input-panel cover |
| LF Nominal Impedance                            | 8Ω                                                                                                   |
| LF Transducer                                   | DVX312A 12-inch (305 mm) woofer                                                                      |
| Max. SPL/1m (calc)                              | 131dB                                                                                                |
| Minimum Impedance                               | 6Ω                                                                                                   |
| Nominal Impedance (Passive)                     | 8Ω                                                                                                   |
| Passive Power Handling                          | 2400W peak                                                                                           |
| Recommended High-Pass Frequency                 | 65Hz                                                                                                 |
| Sensitivity 1 W/1 m                             | 97dB                                                                                                 |
| Shipping Weight                                 | 34.4kg (75.84 lbs)                                                                                   |
| Speaker Type                                    | Full-Range, Two-Way                                                                                  |
| Suspension                                      | (22) M10 threaded suspension points                                                                  |
| System Power Handling (Continuous/Program/Peak) | 600/1200/2400 Watts                                                                                  |
| Weatherized                                     | No                                                                                                   |