

Electro-Voice EVF1122S/94PIB 12 inch 2-Way Full-Range Loudspeaker/SMX Woofer/ND2B Driver/90x40deg/Evcoat/Pi-Weatherized/Black

| | |
|---|---|
| Frequency Range (-10 dB) | 49 - 19000kHz |
| Weight Net | 28.6kg (63.05 lbs) |
| Depth | 413.3mm (16.27") |
| Width | 406.3mm (16") |
| Height | 768.6mm (30.26") |
| Coverage (Nominal -6 dB) H | 90° |
| Coverage (Nominal -6 dB) V | 40° |
| Crossover Frequency | 1450Hz |
| Enclosure Material | 13 Ply Weather Resistant Birch |
| Environmental Specs | Standard versions: IEC 60529 IP44 |
| Frequency Response (-3 dB) | 58 - 16000kHz |
| Grille | Standard versions: 16 GA Galvanneal, Powdercoat, with screen behind |
| HF Transducer | ND2B, 2 in (51 mm) Diaphragm Compression Driver |
| Input Connections | Phoenix/Euroblock style screw terminals |
| LF Transducer | SMX2121, 12 in (305mm) Driver |
| Max. SPL/1m (calc) | 131dB |
| Minimum Impedance | 6Ω |
| Nominal Impedance (Passive) | 8Ω |
| Passive Power Handling | 2000W peak |
| Recommended High-Pass Frequency | 65Hz |
| Sensitivity 1 W/1 m | 98dB |
| Speaker Type | Full-Range, Two-Way |
| Suspension | (22) M10 Threaded Points |
| System Power Handling (Continuous/Program/Peak) | 500/1000/2000Watts |
| Weatherized | No |